

VT-F Industrial Borescope Specifications





Product parameters	
Host parameters	
display screen	10 inch \ 15.6 inch industrial control grade touch LCD screen
Output port	video output, USB output
memory	It comes with a 32G U disk, which can be expanded up to 1T
Power supply	Connect to the power supply to use
Plug standard	GB (default), EU standard, US standard, British standard (except for GB standard, other adapters can be matched)
Brightness lighting	Rear light: 60000 Lux, Front light: 100000Lux
Focus factor	Autofocus
Brightness adjustment	Levels 1-8
Magnification	Levels 1-5
Environmental parameters	
Waterproof rating	IP54
High pressure resistance	not
Operating temperature	-20°C ~ 70°C
Storage temperature	-20°C ~ 60°C
relative humidity	9.5% max, non-condensing
System parameters	
operating system	Windows operating system
file format	Image JPEG (JPG) format, videoMP4 format
File management	Support the creation, renaming, moving, and deletion of files and folders in Chinese and English, and storing them in a USB flash drive and copying them
Supported Languages	Eight Chinese languages are available, including Chinese, English, Russian, Japanese, French, German, Portuguese, and Spanish
Image processing	Adaptive Noise Cancellation, Photo, Video, Negative, Flip, Freeze, Online Editing, Graffiti, Postmark



Product parameters	
Insert the tube	
Camera pixels	1million pixels
Camera orientation	Direct view, side view, double view
Type of lighting	RearED fiber conduction
Camera diameter	1.2mm-6mm
Pipeline length	1m-10m
Field of view (θ).	120°
depth of field	12mm-200mm
Angle (α).	0°/30°/70°/90°
Waterproof rating	IP67
Operating temperature	-20°C ~ 70°C
Pipeline material	alloy
Configure the manifest	
Endoscope host	*1
pipeline	*1
Three-proof box	*1
flash drive	*1
adapter	*1
Warranty card	*1
Instructions	*1
Certificate	*1
Plug converter	Please check the order details for details